

FLOORING365.co.uk

Technical Specification Sheet

Glanwell Engineered Natural Oak Lacquered Wood Flooring (125mm x 18/4mm)

Product Overview

The Glanwell Engineered Natural Oak flooring offers a timeless and elegant appearance, finished with a protective lacquer that enhances durability while maintaining the natural beauty of the wood. The narrower 125mm boards create a more traditional and detailed look, making it a lovely choice for both classic and contemporary interiors.

With its solid 18mm construction, this flooring provides durability and a reassuring feel underfoot, making it well suited to everyday living.

Construction Details

This flooring features a high-quality engineered construction, designed to provide strength, stability, and long-term performance.

- Top layer: 4mm solid oak veneer
- Core: Multi-layered timber or plywood construction
- Base layer: Stabilising backing layer

The thicker wear layer allows for increased durability and the potential for refinishing over time, making it a reliable long-term investment.

Finish & Surface

The lacquered finish provides a smooth and protective surface, ideal for busy households.

- Lacquer forms a durable layer on the surface
- Helps resist spills, stains, and everyday wear
- Creates a clean and consistent appearance

This makes it a practical, low-maintenance option without compromising on style.

Key Specifications

Specification	Details
Product Code	125184LAC1
Flooring Type	Engineered Wood
Wood Species	Oak
Finish	Lacquered
Thickness	18mm
Wear Layer	4mm Solid Oak Top Layer
Board Width	125mm
Board Length	300mm – 1200mm (Mixed Lengths)
Edge Detail	Micro Bevel
Grade	Natural Grade
Profile	Tongue & Groove
Installation Method	Floating (glued joints), Glue-Down or Nail-Down
Pack Coverage	1.2 m ² per pack
Underfloor Heating	Suitable (see guidelines below)
Surface Texture	Smooth Finish
Finish Type	Protective Lacquer
Room Suitability	Living Areas, Bedrooms, Hallways
Commercial Use	Light Commercial

Board Style & Appearance

The 125mm board width offers a classic and detailed aesthetic, ideal for creating a more traditional and characterful look.

Natural variation in tone and grain ensures each board has its own unique appearance, adding to the authenticity of the floor.

Installation Information

This flooring features a **tongue and groove profile**, providing a traditional and secure fit.

Suitable installation methods include:

- Floating installation with glued joints
- Glue-down installation for a more solid feel
- Nail-down installation over timber subfloors

Due to the thickness of the boards, professional installation is recommended for the best results.

Underfloor Heating Compatibility

This flooring is suitable for use with **water-based underfloor heating systems** when installed correctly.

- Maximum surface temperature: 27°C
- Gradual temperature changes are recommended
- Ensure proper subfloor preparation

Electric underfloor heating systems are not recommended unless specifically approved.

Maintenance Overview

To maintain the appearance and longevity of this flooring:

- Clean regularly using a soft brush or vacuum
- Use a damp (not wet) mop
- Avoid harsh chemicals and abrasive cleaners
- Do not use excessive water

For best results, follow a dedicated care and maintenance guide for lacquered wood flooring.

Important Notes

- Flooring must be acclimatised before installation
- Check all boards prior to fitting
- Natural variation in colour and grain is to be expected
- Not suitable for bathrooms or wet areas

Final Thoughts

The Glanwell Engineered Natural Oak flooring combines a traditional narrow board design with a durable lacquered finish. Its premium construction and timeless appearance make it a practical and stylish choice for a wide range of interiors.

Get in touch!

Phone: 0333 002 0175

Email: Sale@flooring365.co.uk

FLOORING365.co.UK