

FLOORING365.CO.UK

Technical Specification Sheet

**Glanwell Engineered Natural Oak Brushed & Lacquered Wood Flooring
(150mm x 18/5mm)**

Product Overview

The Glanwell Engineered Natural Oak flooring offers a timeless and versatile appearance, combining a brushed surface with a durable lacquered finish. The natural oak tones and subtle texture create a balanced look that works beautifully across both traditional and contemporary interiors.

With its solid 18mm construction and engineered design, this flooring provides durability, stability, and a reassuring feel underfoot, making it ideal for everyday living spaces.

Construction Details

This flooring features a high-quality engineered construction, designed to provide strength, stability, and long-term performance.

- Top layer: 5mm solid oak veneer
- Core: Multi-layered timber or plywood construction
- Base layer: Stabilising backing layer

The thicker wear layer offers enhanced durability and allows for refinishing over time, helping extend the lifespan of the floor.

Finish & Surface

The brushed and lacquered finish offers a combination of texture and protection.

- Brushing highlights the natural grain and adds subtle texture
- Lacquer forms a durable protective surface layer
- Helps resist everyday wear, spills, and stains

This creates a floor that is both characterful and easy to maintain.

Key Specifications

Specification	Details
Product Code	150185BRLAC1
Flooring Type	Engineered Wood
Wood Species	Oak
Finish	Brushed & Lacquered
Thickness	18mm
Wear Layer	5mm Solid Oak Top Layer
Board Width	150mm
Board Length	300mm – 1200mm (Mixed Lengths)
Edge Detail	Micro Bevel
Grade	Natural Grade
Profile	Tongue & Groove
Installation Method	Floating (glued joints), Glue-Down or Nail-Down
Pack Coverage	2.16 m ² per pack
Underfloor Heating	Suitable (see guidelines below)
Surface Texture	Brushed
Finish Type	Protective Lacquer
Room Suitability	Living Areas, Bedrooms, Hallways
Commercial Use	Light Commercial

Board Style & Appearance

The 150mm board width offers a classic and versatile appearance, suitable for a wide range of room sizes and interior styles.

Natural variation in tone and grain ensures each board has its own unique character, while the brushed finish adds depth and texture to the overall look.

Installation Information

This flooring features a **tongue and groove profile**, providing a traditional and secure fit.

Suitable installation methods include:

- Floating installation with glued joints
- Glue-down installation for a more solid feel
- Nail-down installation over timber subfloors

Due to the thickness of the boards, professional installation is recommended for the best results.

Underfloor Heating Compatibility

This flooring is suitable for use with **water-based underfloor heating systems** when installed correctly.

- Maximum surface temperature: 27°C
- Gradual temperature changes are recommended
- Ensure proper subfloor preparation

Electric underfloor heating systems are not recommended unless specifically approved.

Maintenance Overview

To maintain the appearance and longevity of this flooring:

- Clean regularly using a soft brush or vacuum
- Use a damp (not wet) mop
- Avoid harsh chemicals and abrasive cleaners

- Do not use excessive water

For best results, follow a dedicated care and maintenance guide for lacquered wood flooring.

Important Notes

- Flooring must be acclimatised before installation
- Check all boards prior to fitting
- Natural variation in colour and grain is to be expected
- Not suitable for bathrooms or wet areas

Final Thoughts

The Glanwell Engineered Natural Oak flooring combines a classic board width with a durable brushed and lacquered finish. Its premium construction and timeless appearance make it a practical and stylish choice for a wide range of interiors.

Get in touch!

Phone: 0333 002 0175

Email: Sale@flooring365.co.uk

FLOORING365.co.UK