

FLOORING365.co.uk

Technical Specification Sheet

Cressington Engineered Smoked Oak Brushed & Lacquered Click-Lock Wood Flooring (165mm x 10/1.2mm)

Product Overview

The Cressington Engineered Smoked Oak flooring offers a rich and contemporary look, combining a brushed surface with a protective lacquered finish. The smoked oak tone introduces deeper, warmer hues, adding depth and character while maintaining a refined and modern appearance.

With its slim 10mm construction and click-lock system, this flooring is designed for ease of installation, making it a practical choice for both professional fitters and DIY projects.

Construction Details

This flooring features a lightweight engineered construction, designed for ease of handling and installation.

- Top layer: 1.2mm solid oak veneer
- Core: High-density fibreboard (HDF)
- Base layer: Stabilising backing layer

The slim profile makes it particularly suitable where floor height is limited, while still offering the natural look of real wood.

Finish & Surface

The brushed and lacquered finish enhances both the texture and colour of the smoked oak.

- Brushing highlights the natural grain and adds subtle texture
- Lacquer forms a protective surface layer
- Helps resist everyday wear, spills, and stains

The smoked finish deepens the tone of the wood, creating a warmer look.

Key Specifications

Specification	Details
Product Code	HDF165SMOK1
Range	Cressington
Flooring Type	Engineered Wood
Wood Species	Oak (Smoked)
Finish	Brushed & Lacquered
Thickness	10mm
Wear Layer	1.2mm Solid Oak Top Layer
Veneer Thickness	1.2mm
Board Width	165mm
Width Category	Wide (151mm-200mm)
Board Length	1200mm
Edge Detail	Micro Bevel
Grade	Mixed
Profile	Click-Lock System
Installation Method	Floating (Click Installation)
Pack Coverage	2.574 m ² per pack
Surface Texture	Brushed
Finish Type	Protective Lacquer

Board Style & Appearance

The 165mm board width falls within the wide category, helping to create a more open and spacious feel within a room.

The smoked oak tone adds depth and richness, while the mixed grade introduces natural variation in knots and grain for a more characterful finish.

Installation Information

This flooring features a **click-lock system**, designed for quick and straightforward installation.

- Boards click together without the need for adhesive
- Installed as a floating floor
- Suitable for most DIY installations

This system allows for faster fitting while still providing a secure and stable result.

Underfloor Heating Compatibility

This flooring is suitable for use with **water-based underfloor heating systems** when installed correctly.

- Maximum surface temperature: 27°C
- Gradual temperature changes are recommended
- Ensure proper subfloor preparation

Electric underfloor heating systems are not recommended unless specifically approved.

Maintenance Overview

To maintain the appearance and longevity of this flooring:

- Clean regularly using a soft brush or vacuum
- Use a damp (not wet) mop
- Avoid harsh chemicals and abrasive cleaners
- Do not use excessive water

For best results, follow a dedicated care and maintenance guide for lacquered wood flooring.

Important Notes

- Flooring must be acclimatised before installation
- Check all boards prior to fitting
- Natural variation in colour, grain, and knots is to be expected (mixed grade)
- Not suitable for bathrooms or wet areas

Final Thoughts

The Cressington Engineered Smoked Oak flooring combines a rich, modern colour tone with a practical and easy-to-install design. Its brushed and lacquered finish offers both texture and durability, making it a stylish and reliable choice for a wide range of interiors.

Get in touch!

Phone: 0333 002 0175

Email: Sale@flooring365.co.uk

FLOORING365.co.UK